APPLICATION

FOR

UNITED STATES LETTERS PATENT

TITLE: METHODS AND APPARATUS FOR SELECTING
            BASEBAND FILTER PASSBAND FREQUENCY AND
            LOCAL OSCILLATOR FREQUENCIES

INVENTORS: ZHIWEI DONG; RAMIN KHOINI-POORFARD

Express Mail No._____ EV 337934494 US

Date:_____ March 31, 2004

METHODS AND APPARATUS FOR SELECTING BASEBAND FILTER PASSBAND FREQUENCY AND LOCAL OSCILLATOR FREQUENCIES

Reference to Earlier Application

This application is a continuation-in-part of U.S.

5   Patent Application serial number 10/412,871, filed

April 14, 2003, entitled "Integrated Multi-Tuner Satellite

Receiver Architecture and Associated Method" by Ramin

Khoini-Poorfard and Andrew W. Krone.

Technical Field of the Invention

10   The present invention relates to receiver

architectures for high frequency transmissions and more

particularly to set-top box receiver architectures for

satellite television communications.

Background

15   In general, an ideal receiver architecture for an

integrated circuit from a bill-of-material point of view is

usually a direct down conversion (DDC) architecture.

However, in practice, there are several issues that often

prohibit the practical design of integrated circuits using

20   DDC architectures. These issues typically include DC

offset voltage and 1/f noise from baseband circuitry

located on the integrated circuit. In mobile applications,

such as with cellular phones, the DC offset voltage is a

time varying entity which makes its cancellation a very

difficult task. In other applications where mobility is not a concern, such as with satellite receivers, the DC offset voltage can be stored and cancelled, such as through the use of external storage capacitors. However, 1/f noise is still an issue and often degrades CMOS satellite tuners that use DDC architecture.

Conventional home satellite television systems utilize a fixed dish antenna to receive satellite communications. After receiving the satellite signal, the dish antenna circuitry sends a satellite spectrum signal to a satellite receiver or set-top box that is often located near a television through which the viewer desires to watch the satellite programming. This satellite receiver uses receive path circuitry to tune the program channel that was selected by the user. Throughout the world, the satellite channel spectrum sent to the set-top box is often structured to include 32 transponder channels between 950 MHz and 2150 MHz with each transponder channel carrying a number of different program channels. Each transponder will typically transmit multiple program channels that are time-multiplexed on one carrier signal. Alternatively, the multiple program channels may be frequency multiplexed within the output of each transponder. The total number of received program channels considering all the transponders together is typically well over 300 program channels.

Conventional architectures for set-top box satellite receivers include low intermediate-frequency (IF) architectures and DDC architectures. Low-IF architectures utilize two mixing frequencies. The first mixing frequency is designed to be a variable frequency used to mix the selected satellite transponder channel to a pre-selected IF frequency close to DC, and the second mixing frequency is designed to be the low-IF frequency used to mix the satellite spectrum to DC. Direct down conversion (DDC) architectures utilize a single mixing frequency. This mixing frequency is designed to be a variable frequency that is used to mix the selected satellite transponder channel directly to DC.

DDC architectures, however, suffer from disadvantages such as susceptibility to DC noise, 1/f noise and I/Q path imbalances. DDC architectures also often use narrow-band phase-lock-loop circuitry (PLLs), which typically utilize LC-based voltage controlled oscillators (VCOs). Low-IF architectures, like DDC architectures, also typically require the use of such narrow-band PLLs with LC-based VCOs. Such LC-based VCOs are often difficult to tune over wide frequency ranges and often are prone to magnetically pick up any magnetically radiated noise. In addition, interference problems arise because the center frequency for the selected transponder channel and the DDC mixing signal are typically at the same frequency or are very

3

close in frequency. To solve this interference problem,
some systems have implemented receivers where the DDC
mixing frequency is double (or half) of what the required
frequency is, and at the mixer input, a divider (or

5   doubler) translates the DDC mixing signal into the wanted
frequency. Furthermore, where two tuners are desired on
the same integrated circuit, two DDC receivers, as well as
two low-IF receivers, will have a tendency to interfere
with each other, and their VCOs also have a tendency to

10   inter-lock into one another, particularly where the
selected transponder channels for each tuner are close
together.

Another problem exists in satellite receivers
regarding use of a baseband filter. As bandwidth of the

15   baseband filter increases, the bandwidth problems of
amplifiers or transconductors used in the filter makes
design of the filter difficult. Similarly, the larger the
bandwidth of the baseband filter, analog-to-digital (ADC)
sampling rates may also be raised, making system design

20   more difficult. Thus a need exists to avoid interference
between multiple VCOs and a further need exists to reduce
the passband width of a baseband filter of a receiver.

Summary of the Invention

In one embodiment, the present invention includes a

25   method and apparatus to receive satellite signal spectrums
and determine multiple local oscillator (LO) frequencies

4

that do not interfere with each other. Further, in
selecting one or more new LO's for new channels to be
tuned, selected LO's for present channels need not be
changed. Further, the LO frequencies may be selected to be
5   outside of the signal band of a respective signal channel,
yet the down-converted signal channel will be within the
passband width of an associated baseband filter of the
receiver. Also, the present invention includes methods to
determine appropriate bandwidths for baseband filters and
10   an LO step frequency between different LO frequencies.

Brief Description of the Drawings

It is noted that the appended drawings illustrate only
exemplary embodiments of the invention and are, therefore,
not to be considered limiting of its scope, for the
15   invention may admit to other equally effective embodiments.

FIG. 1A is a block diagram for an example satellite
set-top box environment within which the receiver
architecture of the present invention could be utilized.

FIG. 1B is a block diagram for example satellite set-
20   top box circuitry that may include a receiver architecture
according to the present invention.

FIG. 1C is a block diagram of basic receiver
architecture according to the present invention utilizing a
large-step local oscillator.

FIG. 2A is a diagram of an example channel spectrum signal having LO frequency selection regions in accordance with one embodiment of the present invention.

FIG. 2B is a diagram of an example channel spectrum signal having LO frequency selection regions in accordance with a second embodiment of the present invention.

FIG. 2C is a diagram of an example channel spectrum signal having a third signal channel with a worst case selection of LO frequencies.

FIG. 2D is a diagram of an example channel spectrum signal having a third signal channel with a selection of LO frequency in accordance with one embodiment of the present invention.

FIG. 3A is a flow diagram of a method for selecting a LO frequency in accordance with one embodiment of the present invention.

FIG. 3B is a flow diagram of a method for selecting a LO frequency in accordance with a second embodiment of the present invention.

FIG. 3C is a flow diagram of a method for selecting a LO frequency in accordance with a third embodiment of the present invention.

FIG. 3D is a flow diagram of a method for selecting a LO frequency in accordance with a fourth embodiment of the present invention.

FIG. 4 is an example embodiment for the basic receiver architecture using a wide-band analog-to-digital converter and a narrow band tunable bandpass analog-to-digital converter, respectively.

5   FIG. 5 is a block diagram for a two receiver architecture located on a single integrated circuit in accordance with one embodiment of the present invention.

FIG. 6 is a block diagram for a four receiver architecture located on a single integrated circuit in
10   accordance with one embodiment of the present invention.

Detailed Description

The present invention provides single and multi-tuner receiver architectures and associated methods to provide
15   initial analog course tuning of desired channels within a received signal spectrum. Also, the present invention provides algorithms to determine suitable bandwidths for a baseband filter of the receiver, a local oscillator (LO) step frequency, and other parameters to be used in
20   selecting LO frequencies for use in down mixing an incoming signal spectrum.

In the description below, the signal spectrum is primarily described with respect to a satellite transponder channel spectrum; however, embodiments of the present
25   invention may be used with other channel signal spectrums utilized by other systems, if desired.

FIG. 1A is a block diagram for an example satellite set-top box environment 170 within which the receiver or tuner architecture 100 of the present invention could be utilized. In the embodiment depicted, a satellite set-top box 172 receives an input signal spectrum from satellite dish antenna circuitry 171. The satellite set-top box 172 processes this signal spectrum in part utilizing the receiver/tuner circuitry 100. The output from the satellite set-top box 172 is then provided to a television, a videocassette recorder (VCR) or other device as represented by the TV/VCR block 174.

FIG. 1B is a block diagram for example circuitry for a satellite set-top box 172 that could include the receiver architecture 100 of the present invention. The input signal spectrum 107 can be, for example, 32 transponder channels between 950 MHz and 2150 MHz with each transponder channel carrying a number of different program channels. This signal spectrum 107 can be processed by the receiver/tuner 100 to provide digital baseband output signals 112 that represent a tuned transponder channel. These output signals 112 can then be processed by a demodulator 180 that can tune one of the program channels within the tuned transponder channel. The output signal 181 from the demodulator, which represents a tuned program channel within the transponder channel that was tuned by the receiver/tuner 100, can then be processed with a

forward error correction decoder 182 to produce a digital

output stream. This digital output stream is typically the

data stream that is stored by personal video recorders

(PVRs) for later use and viewing by a user, as represented

5   by the PVR output stream 188. The output of the decoder

182, or the stored PVR data as represented by PVR input

stream 192, can then be processed by video/audio processing

circuitry 184 that can include processing circuitry such as

an MPEG decoder. The output of the processing circuitry

10   184 is typically the digital video data stream that

represents the program channel and is used for picture-in-

picture (PnP) operations, for example, where the set-top

box circuitry 172 includes two tuners with one tuner

providing the primary viewing feed and a second tuner

15   providing the PnP viewing feed. The output of the

processing circuitry 184, as well as a PnP input stream 194

from a second tuner if a second tuner is being utilized for

PnP operations, can be processed by a video/audio

controller 186 to generate a video output signal 176 that

20   can subsequently be utilized, for example, with a TV or

VCR. Additional tuners could also be used, if desired.

FIG. 1C is a block diagram of basic receiver

architecture 100 according to the present invention

utilizing a large-step LO circuitry 106. Input signal 107,

25   for example from a satellite dish antenna or other source,

is received and passed through a low noise automatic-gain

amplifier (LNA) 105. In the embodiments described herein, it is assumed that the input signal 107 is a signal spectrum that includes multiple channels, such as a satellite television signals that includes 32 transponder channels between the frequencies of 950 MHz and 2150 MHz. The output signal 108 from LNA 105 is initially tuned with analog coarse tune circuitry 102 utilizing a LO mixing frequency (f_{LO}) provided by large-step LO circuitry 106. The large-step LO circuitry 106 also receives a coarse channel selection signal 162.

As discussed below, signal 162 may be determined based on a desired passband of a baseband filter and consideration of avoidance of noise and interference from LO circuitry associated with other receivers. The resulting coarsely tuned signal 110 is then subjected to digital fine tune circuitry 104 utilizing the center frequency (f_{CH}) 114 (also referred to herein as "f_{signal}") for the desired channel to produce digital baseband signals 112. The digital fine tune circuitry 104 may include an analog-to-digital converter (ADC) and a baseband filter.

In certain embodiments, coarse tune circuitry 102 may include two mixers to generate an output Q signal that is offset by a phase shift of 90 degrees from an output I signal. To provide these two signals, a LO mixing frequency (f_{LO}) and a dual divide-by-two and quadrature shifter (÷2/90°) may be used. In other embodiments, other

manners of frequency division, such as a divide-by-four operation, may be used. Also, no frequency division may be used in other embodiments such that the LO mixing frequency (f_{LO}) 116 is directly used to down mix I and Q signals.

5   The large-step local oscillator 106 may generate a mixing signal at one of a plurality of predetermined frequencies. The output LO frequency is selected based upon the channel within the spectrum that is desired to be tuned. The output LO frequencies can be organized and

10   uniformly or non-uniformly spaced as desired. As one example, the output LO frequencies can be a fixed bandwidth apart from each other and can span the entire input channel spectrum signal 108. The local oscillator mixing frequency (f_{LO}) 116 may be generated using phase-lock-loop (PLL)

15   circuitry, in one embodiment. In such an embodiment, a voltage controlled oscillator (VCO), such as an LC-tank oscillator or an RC-based oscillator may be used.

     In various embodiments, a baseband filter's passband and LO step frequency (i.e., a step frequency between

20   candidate LO frequencies) for two or more satellite tuners may be selected to acquire the required signals, to eliminate the effects of 1/f noise and DC offset voltage, to avoid cross talk of the VCOs used in the large step LO circuitry 106, to avoid the harmonic of one VCO affecting

25   other VCOs, and to cancel input signal channel frequency errors.

Referring now to FIG. 2A, shown is a diagram of an example satellite signal spectrum in accordance with one embodiment of the present invention. As shown in FIG. 2A, satellite spectrum 108 includes a first signal channel 200 that is within a first frequency region 210 (i.e., frequency region B). Frequency region 210 is surrounded by two adjacent frequency regions, namely frequency region A 220 and frequency region C 215. As will be discussed further below, frequency region A 220 and frequency region C 215 may be used as LO frequency selection regions, and one or both of these regions may include a LO frequency that is to be used to downmix first signal channel 200 to a frequency near DC.

As shown in FIG. 2A, first signal channel 200 has a bandwidth smaller than the bandwidth of frequency region 210. This is because frequency region 210 includes a pair of offset frequencies 205 (i.e., $f_{noise-offset}$) that may be used to offset a LO frequency from one of regions A and C to avoid 1/f noise and DC offset voltage noise. As shown in FIG. 2A, frequency region B 210 has a bandwidth equal to f_w, which is the frequency width of the signal channel, taking into account noise offset regions 205. In various embodiments, the value of offset regions 205 may vary. In certain embodiments, offset regions 205 may be between approximately 8 and 10 MHz, although the scope of the present invention is not so limited.

12

Similarly, shown in FIG. 2A, a passband width f_B of a baseband filter which may be used to filter the downmixed signal may be equal to the width of region B 210 (i.e., f_W) and either one of regions A 220 or region C 215. Thus, it is desired that a LO frequency used to downmix signal channel 200 be located within region A 220 or region C 215 so that information contained in signal channel 200 is obtained without information loss.

That is, if there is no LO frequency located in regions A or C, the LO frequency will either: (1) locate in region B, which causes a loss of information; (2) or locate outside of regions A and C, which makes the signal frequency locate outside of the passband of the filter and causes that part of the signal to be attenuated. As seen in FIG. 2A, the width of regions A, B and C totally is $2f_B-f_W$, and the width of regions A or C are same: f_B-f_W. For a given f_B and a LO step frequency ($f_{LO-step}$), a smaller f_W makes regions A and C wider, and makes the number of LO frequencies in regions A and C larger.

In a continuous frequency band with a channel width of f, the smallest possible number (N_s) of LO frequencies and the largest possible number (N_l) of LO frequencies have the following relationship:

$$f = N_s \bullet f_{LO-step} + df, N_l = N_s + 1, 0 \leq df \leq f_{LO-step} \quad (EQ1).$$

Table 1 below shows the smallest passband frequency (f_B) of a baseband filter for a given Ns_{AC}, f_W, and $f_{LO-step}$,

13

where m is any possible positive integer. As discussed above, a smaller f_B is desired to improve receiver performance and simplify design.

Table 1

Ns_{AC}	1	2	3	4	5
$f_B - f_w - f_{noise-offset}$	$f_{LO-step} - df_{fw}/2$	$f_{LO-step}$	$2f_{LO-step} - df_{fw}/2$	$2f_{LO-step}$	$3f_{LO-step} - df_{fw}/2$
Best $f_B - f_w$	$1/2 f_{LO-step}$	$f_{LO-step}$	$3/2 f_{LO-step}$	$2f_{LO-step}$	$5/2 f_{LO-step}$
Best $f_{LO-step}$	f_w/m	n/a	f_w/m	n/a	f_w/m

5   From Table 1, the expression for f_B is:

$$f_B \geq f_W + f_{noise-offset} + \frac{N_{s_{AC}}}{2} \bullet f_{LO-step} + \frac{(-1)^{N_{s_{AC}}+1} + 1}{4} \bullet (f_{LO-step} - df_W) \quad (EQ2)$$

, where Ns_{AC} is the smallest number of LO frequencies in regions A and C.

10   Referring now to FIG. 2B, shown is an example satellite signal spectrum showing a crosstalk region in accordance with an embodiment of the present invention. Such an embodiment may be, for example, a two tuner receiver. As shown in FIG. 2B, satellite spectrum 108

15   includes a first frequency region B 210 that includes a second signal channel 200 with a center frequency of $f_{signal2}$ that is desired to be tuned by a receiver. Note that for simplicity, in FIG. 2B the noise-offset regions 205 of FIG. 2A are not shown, however, it is to be understood that such

14

regions may be present to prevent noise in a desired channel signal, and it is understood that f_W may include these offset regions.

As shown in FIG. 2B, a first LO frequency (f_{Lo1}) is present in second signal channel 200. When the second signal channel 200 is desired to be acquired, a second LO frequency (f_{LO2}) may be selected. In various embodiments, the second LO frequency should be separated from the first LO frequency (f_{LO1}) by at least an amount equal to $f_{separate}$ to avoid crosstalk between the two VCOs for the two LO frequencies. As shown in FIG. 2B, a crosstalk region 230 may be equal to two times $f_{separate}$. While the width of a crosstalk region may vary, in certain embodiments such a crosstalk region may be between approximately 60-70 MHz wide, although the scope of the present invention is not so limited. If the second LO frequency is selected from within crosstalk region 230, crosstalk may occur between the two VCOs. Accordingly, in various embodiments the second LO frequency may be selected from region 225 or region 218, which are subregions within region A 220 and region C 215, respectively, that exist outside of crosstalk region 230.

In certain embodiments, the crosstalk problem may be resolved by setting $f_{LO-step}$ larger than $f_{separate}$ such that there is no crosstalk, regardless of which LO frequency is chosen. In other embodiments, $f_{LO-step}$ may be made smaller

15

and the number Ns_{AC} made larger to avoid crosstalk. Normally, a smaller $f_{LO-step}$ may cause a smaller filter bandwidth and ADC sampling frequency, which make circuit design easier. A larger $f_{LO-step}$ may be selected only when a smaller $f_{LO-step}$ does not make the filter bandwidth and ADC sampling frequency smaller, in certain embodiments.

If $f_{LO-step}$ is selected to be larger than $f_{separate}$, two situations may exist: (1) the second signal can use the LO of the first channel (e.g., using a MUX); and (2) the second signal does not use the first channel LO (i.e., no MUX is used). In various embodiments, it may be desirable to avoid use of a MUX in such a two tuner receiver.

For the first situation to avoid a worst case in which f_{signal} is as far away as possible from the nearest LO frequency not in the second channel, $f_{LO-step}$ may be set to be slightly larger so $f_{LO-step}$ times some integer is larger than f_W, so that there is at least one LO frequency available in region A or C. Then from Table 1, where $Ns_{AC}=1$, f_B may be determined.

For the second situation, $Ns_{AC}=1$ cannot be selected, otherwise there may be only one LO frequency for the second signal, and if this frequency is the same as the LO frequency for the first signal channel, there is no choice for the second signal. So $Ns_{AC}=2$ is selected, and from Table 1, the smallest f_B is:

$$f_B \geq f_{separate} + f_W \qquad\qquad (EQ3).$$

16

In embodiments where $f_{LO-step}$ is smaller than $f_{separate}$, there are two situations that may occur. First, the crosstalk region of the first LO covers all or part of one of the two LO selection regions (i.e., region A or region C) of a second signal channel; second, the crosstalk area covers part of both regions A and C. (The crosstalk area cannot cover all of regions A and C, otherwise there would be no LO frequency choice for the second channel.)

For the first situation, the LO frequencies in one of the two LO selection regions (region A or region C) cannot be used. Since there is at least one LO frequency to be used for the second channel, Ns_{AC} is at least 2. From Table 1, another limitation for f_B is:

$$f_B \geq f_{LO-step} + f_W \qquad (EQ4).$$

The second situation occurs when $f_{separate} > f_W/2$, otherwise, the crosstalk area cannot cover part of both region A and region C. The LO frequency that can be used for a second signal and is nearest to $f_{signal2}$, and which should be $Nl_{separate} \bullet f_{LO-step}$ away from f_{LO1}. In this case, f_B is:

$$f_B \geq Nl_{separate} \bullet f_{LO-step} + f_W / 2 - \left| f_{signal2} - f_{LO1} \right| \qquad (EQ5)$$

where $\left| f_{signal2} - f_{LO1} \right| \geq 0$. So the worst case is $\left| f_{signal2} - f_{LO1} \right| = 0$, and f_B is:

$$f_B \geq Nl_{separate} \bullet f_{LO-step} + f_W / 2 \qquad (EQ6).$$

17

Since $Nl_{separate} \bullet f_{LO-step} = f_{separate}$ occurs only when $f_{separate}$ is some integer times $f_{LO-step}$, the equality is valid. Selecting $f_{LO-step}$ such that $f_{separate}$ is an integer multiple of $f_{LO-step}$ can therefore make f_B smaller.

5   Comparing Equation 3 with Equation 4 and Equation 6, $f_{LO-step} < f_{separate}$ may make f_b smaller and thus no MUX is needed for Equation 4 and Equation 6. Thus for a two tuner system, $f_{LO-step} < f_{separate}$ is used, and no MUX is needed in any such case.

10   In designing a multi-tuner receiver having more than two tuners (and therefore more than 2 LO frequencies are desired), crosstalk between the VCOs may be avoided in similar fashion to the two VCO embodiment discussed above. In certain embodiments, two situations may be present: (1)

15   one LO frequency can be used for several signal channels; and (2) one LO frequency can be used only for one signal channel.

In the first situation, suppose there are N TV channels that potentially may be tuned using an N tuner

20   receiver. According to the first situation, one LO frequency may be used for several of the N signal channels. In such an embodiment, for $f_{LO-step}$ larger than $f_{separate}$, crosstalk issues are not applicable and one LO frequency may be used for several channels. Then, there are no

25   limits on the LO selection. Accordingly, Ns_{AC} may be selected to be equal to one. Then using Table 1 above, the

18

appropriate f_B may be obtained. As discussed above, a smaller $f_{LO-step}$ may make f_b smaller (or better).

For a three tuner receiver, now consider $f_{LO-step} <$ $f_{separate}$ where a MUX is used. If N=3, the worst case for f_B is the case of the largest distance between the first two LO frequencies when the LO frequency for the third channel must be selected from one of these two LO frequencies, for which $f_B \geq f_w + f_{separate}$. Referring now to FIG. 2C, shown is a diagram of a signal spectrum that may occur in a three tuner receiver in a worst case situation where a second LO frequency is not carefully selected. As shown in FIG. 2C, a third signal channel 250 has a width of f_w. Further shown in FIG. 2C is a first local oscillator frequency (f_{LO1}) having a crosstalk region (i.e., crosstalk region 1) 260 and a second LO frequency (f_{LO2}) having a crosstalk region (i.e., crosstalk region 2) 270.

Fortunately, this worst case may be eliminated by first carefully selecting the second LO frequency (f_{LO2}). Referring now to FIG. 2C, if the second signal channel is on the right side of the f_{LO2} frequency, then another LO with a larger frequency may be chosen; then there are more LO choices between the first two LO's. If it is on the left side of f_{LO2}, since $f_{LO-step}$ is smaller than $f_{separate}$, another choice is available between these two worst case LO's for the second LO. Thus the new distance between the first two

19

LO's with no LO available for the third signal gets smaller.

Referring now to FIG. 2D, shown is a diagram of a satellite signal spectrum for a three channel tuner in accordance with an embodiment of the present invention. As shown in FIG. 2D, the second LO frequency may be carefully selected to eliminate the worst case as shown above in FIG. 2C. Accordingly, as shown in FIG. 2D, a second LO frequency may be selected to be about $f_w + f_{separate}$ away from f_{LO1}.

At this case,

$$f_B \geq f_w/2 + (Nl_{separate} + Nl_{fw}) \cdot f_{lo-step}/2 \geq f_w + 1/2 f_{separate} \quad [EQ\ 6.1]$$

where $Nl_{separate}$ is the largest number of possible LO frequencies located in a frequency region of $f_{separate}$. Thus the worst case for the third LO frequency may be eliminated by choosing f_{LO2} carefully. Normally, the value of Equation 6.1 is smaller than $F_w + f_{separate} - df_w/2$ (from Table 1), so $f_{LO-step} < f_{separate}$ may be selected.

For the situation where no MUX is used, and $f_{LO-step} >= f_{separate}$, the worst case is that three signals may be present at the exact same frequency, which means there must be 3 LO's in region A and region C. From Table 1, we get

$$f_B \geq fw + 2_{fseparate} - \frac{dfw}{2} \quad (EQ7).$$

When $f_{LO-step} < f_{separate}$, the worst case is the same as the worst case when one LO can be used for several channels, except

20

the third LO cannot select one of the first two LO's, which
is shown in FIG. 2D. Thus, the third LO must be $f_{separate}$
apart from f_{LO1} or f_{LO2}. Thus:

$$f_B \geq \frac{fw}{2} + (3Nl_{separate} + Nl_{fw}) \bullet \frac{f_{lo-step}}{2} \qquad (EQ8).$$

5   Normally, (EQ8) ≤ (EQ7) so $f_{LO-step} < f_{separate}$ can make f_B
smaller (better), and thus $f_{LO-step} < f_{separate}$ is used.

From the above analysis, for N=2, f_B can get fw/2
smaller (or better) when $f_{LO-step} < f_{separate}$ is chosen instead
of $f_{LO-step} >= f_{separate}$. For N=3, f_B can get better for $f_{LO-step}$
10   < $f_{separate}$, but at some special case, f_B is the same for $f_{LO-step} < f_{separate}$ and $f_{LO-step} >= f_{separate}$.

When N ≥ 4 and $f_{LO-step} \geq f_{separate}$, f_B may be the same
(i.e., no worse) as f_B when $f_{LO} < f_{separate}$. In such manner,
when using a MUX, f_B may be chosen using $Ns_{AC} = 1$ in Table 1
15   (meaning there is only one available LO in regions A and
C). Thus when a first signal channel is received, its
available LO may be chosen from its available LO's (i.e.,
one or two available LO's). When the next signal channel
is received, if its available LO is the same as an earlier
20   signal's LO, that LO may be multiplexed to the new signal
channel. Otherwise, the available LO for that channel may
be used.

In certain embodiments when N ≥ 4 and $f_{LO-step} \geq f_{separate}$
and no MUX is available, f_B may be chosen using $Ns_{AC} = N$ in
25   Table 1 (meaning there are N LO frequencies available in

21

regions A and C). In such manner, when a first signal is received, one of its N available LO's is chosen. When a next channel is received, its LO is chosen to be a frequency not occupied by the earlier signal.

5   Because of a frequency error of the LO in a low noise blockdown converter (LNB) of a satellite receiver, there is some error for the center frequency (f_{signal}) of the signal channel. Since tuning methods in accordance with embodiments of the present invention are related to the

10   center frequency of the signal channel, this error may affect tuning. There are two ways to eliminate this error. First, the error may be considered in the frequency for 1/f noise and DC offset, which makes this frequency larger, and thus may make the passband frequency of baseband filter

15   larger. Second, after this error is known, the channel is re-tuned using the error. In certain embodiments, this may be preferable, because only a first acquired channel need be re-tuned, and re-tuning when watching TV is not necessary, as the error may be saved in a storage medium of

20   the system (e.g., a nonvolatile memory or the like). Then, when the TV is turned on, this error may be automatically used to correct the center frequency of the signal channel.

       In various embodiments, a harmonic of one VCO near the frequency of a second VCO may be avoided in like manner to

25   avoiding VCO crosstalk. That is, if one VCO's harmonic frequency is near another VCO, some crosstalk may occur.

22

The area of harmonic frequency which causes crosstalk may simply be treated as another crosstalk region. Normally, this crosstalk region affects LO frequency selection only when the two used LO frequencies are close to one another,

5   and one is from a VCO frequency divided by 4, and the other is from another VCO frequency divided by two. Since this harmonic crosstalk area is much smaller than the original crosstalk region, if the original crosstalk region is considered in LO frequency selection, this harmonic

10   crosstalk area is covered automatically.

Another issue is that when one LO frequency derived from a VCO frequency divided by four and this VCO frequency divided by two is still located in the signal channel (i.e., there are at least two crosstalk regions for one LO

15   frequency). Fortunately, these two crosstalk regions are at least 0.9 GHz apart, and only one of them affects LO frequency selection. When the LO frequency is selected, only the crosstalk region affecting the selection should be considered.

20   By now, all analysis for selecting a baseband filter's passband frequency and LO step frequency has been described. Table 2 below provides the best choices for a filter's passband frequency by carefully choosing LO step frequencies for a given number of tuners (N), and number of

25   LO's for a given VCO.

Table 2

# of Tun-ers	# of LO's for one VCO	f_B expression	Best $f_{LO\text{-step}}$	Best f_B	Condition
N=1	1	$f_w + f_{LO-step} - (df_{fw})/2$	f_w / m	$f_w + f_{LO-step}/2$	m as larger as possible
N=2	1 and 2	$f_w/2 + Nl_{separate} \bullet f_{LO-step}$	$f_{separate}/m$	$f_{separate} + f_w/2$	$f_w < 2 \bullet f_{separate}$
		$f_w + f_{LO-step}$	as small as possible	$f_w + f_{LO-step}$	$f_w \geq 2 \bullet f_{separate}$
N=3	Sev-eral	$f_w/2 + (Nl_{separate} + Nl_{fw}) \bullet f_{LO-step}/2$	$f_w/m1$ and $f_{separate}/m2$	$f_w + f_{separate}/2$	n/a
	1	$(f_w + (3 \bullet Nl_{separate} + Nl_{fw}) \bullet f_{LO-step})/2$	$f_w/m1$ and $f_{separate}/m2$	$f_w + 3 \bullet f_{separate}/2$	n/a
N≥4	Sev-eral	$f_w + f_{LO-step} - dfw/2$	$f_{separate}$	$f_w + f_{separate}/2$	n/a
N≥4 ev-en	1	$f_w + \dfrac{N}{2} \bullet f_{LO-step}$	$f_{separate}$	$f_w + \dfrac{N}{2} \bullet f_{separate}$	n/a
N≥4 odd	1	$f_w + ((N \bullet Nl_{separate} + 1) \bullet f_{LO-step} - df_w/2$	$f_w/m1$ and $f_{separate}/m2$	$f_w + \dfrac{N}{2} \bullet f_{separate}$	n/a

When $f_{noise\text{-}offset}$ for 1/f noise and DC offset is considered, all f_w's in Table 2 may be replaced by $f_w + 2f_{noise\text{-}offset}$, and

5   the resulting f_B minus $f_{noise\text{-}offset}$ is the final passband frequency of the filter.

Thus in various embodiments, in designing a multi-tuner receiver a baseband filter's passband frequency and LO step frequency may be selected to make the best choice for an unavoidable worst case condition for a given number of tuners present in the receiver.

Embodiments of the present invention may also implement a LO tuning algorithm that essentially tries to find the best choice for a given condition. The considerations behind the algorithm are: (1) to avoid 1/f noise and DC offset, the LO frequency should be at some distance away from the signal channel; and (2) the performance of the baseband filter requires the LO frequency to be as near as possible to the signal channel to make group delay and passband attenuation smaller.

Based on these considerations, an algorithm in accordance with an embodiment of the present invention may make the center frequency of the signal channel (i.e., f_{signal}) at the middle of the passband of the filter. To make this possible, any given signal channel may be considered as the widest channel for the signal spectrum, and the LO frequency may be selected accordingly. If

$$f_{signal} = Ns_{signal} \bullet f_{LO-step} + df_{signal} , \; f_{WW}/2 = Ns_{f_{WW}/2} \bullet f_{LO-step} + d \frac{f_{WW}}{2} \quad (EQ9)$$

where f_{WW} is the frequency width of the widest signal channel. Let:

$$Ns_{channel} = Ns_{f_{WW}/2} , \; df_{channel} = d \frac{f_{WW}}{2} \quad (EQ10)$$

25

Then, the LO frequency should satisfy the following equations:

$$f_{LO} \leq f_{signal} - f_{WW} / 2 = (Ns_{signal} - Ns_{channel}) \bullet f_{LO\text{-}step} + (df_{signal} - df_{channel}) \quad (EQ11)$$

$$f_{LO} \geq f_{signal} + f_{WW} / 2 = (Ns_{signal} + Ns_{channel}) \bullet f_{LO\text{-}step} + (df_{signal} + df_{channel}) \quad (EQ12)$$

5   Since $df_{signal} - df_{channel}$ may be larger or smaller than zero, and $df_{signal} + df_{channel}$ may be larger or smaller than $f_{LO\text{-}step}$, four possible LO frequencies, $Ns_{signal} - Ns_{channel} - 1$, $Ns_{signal} - Ns_{channel}$, $Ns_{signal} - Ns_{channel} + 1$, and $Ns_{signal} - Ns_{channel} + 2$, may be selected for the first incoming signal channel or un-affect

10   a second channel by the crosstalk region of the first LO frequency. The conditions for the LO frequencies are shown in Table 3.

Table 3

N_{LO}	Conditions		
	$df_{channel} - df_{signal}$	$df_{channel} + df_{signal} - f_{LO\text{-}step}$	$df_{signal} - f_{LO\text{-}step}/2$
$Ns_{signal} - Ns_{channel} - 1$	>0	>0	<0
$Ns_{signal} - Ns_{channel}$	<=0	<0	<=0
	<0	>0	>0
$Ns_{signal} + Ns_{channel} + 1$	<0	<0	>=0
	>=0	<0	<0
$Ns_{signal} + Ns_{channel} + 2$	>0	>0	>0

15   For a second TV signal channel, three situations may exist: (1) no effect by the crosstalk region of the first LO frequency; (2) the crosstalk region affects possible LO frequencies on one side of the second signal channel; and

26

(3) the crosstalk region affects all possible LO
frequencies on both sides of the second signal channel. A
flag may be used to show which side of the signal channel
is affected by the crosstalk region of first LO frequency;
5   if the flag is positive, then the left side of the signal
channel is affected; if the flag is negative; the right
side of the signal channel is affected, although the scope
of the present invention is not so limited. Ns_{AC} and $df_{channel}$
may be redefined when both sides of the signal channel are
10   affected, as shown in Table 4. The possible LO frequencies
for the second signal channel and the conditions for the
frequencies are shown in Table 5.

Table 4

Condition	no effect on the first LO	affecting one side	affecting both sides
Expression	$\left\| f_{signal2} - f_{LO1} \right\| \geq Nl_{separate} + f_{WW} / 2$	$\left\| f_{signal2} - f_{LO1} \right\| \geq Nl_{separate} - f_{WW} / 2$	$\left\| f_{signal2} - f_{LO1} \right\| < Nl_{separate} - f_{WW} / 2$
$df_{channel}$	$d(f_{WW} / 2)$	$d'(f_{WW} / 2)$	$d(f_{separate} - \left\| f_{signal2} - f_{LO1} \right\|)$
$Ns_{channel}$	$Ns_{(f_{WW} / 2)}$	$Ns_{(f_{WW} / 2)}$	$Ns_{(f_{separate} - \left\| f_{signal2} - f_{LO1} \right\|)}$
flag	n/a	$f_{signal2} - f_{LO1}$	$f_{signal2} - f_{LO1}$

15   The conditions for the signal channel tuning algorithm for
a second signal channel which is affected by a first LO
frequency is shown in Table 5 below:

Table 5

N_{LO}	Conditions
$Ns_{signal} - Ns_{channel} - 1$	flag <0 and $df_{signal} < df_{channel}$
$Ns_{signal} - Ns_{channel}$	flag <0 and $df_{channel} \leq df_{signal}$
$Ns_{signal} + Ns_{channel} + 1$	flag >0 and $df_{channel} \leq f_{LO-step} - df_{signal}$
$Ns_{signal} + Ns_{channel} + 2$	flag >0 and $f_{LO-step} - df_{signal} < df_{channel}$

Referring now to FIG. 3A, shown is a flow diagram of a method for tuning a satellite receiver in accordance with one embodiment of the present invention. Specifically, FIG. 3A shows a method 300 that may be used to tune a first

5 signal channel desired by a user of a satellite receiver that has two tuners. As shown in FIG. 3A, method 300 may begin by receiving a selection signal for a first signal channel (block 305). Such a selection signal may be received from a user who desires to watch a given TV

10 channel.

A first LO frequency may be selected that is outside of the first signal channel (block 310). By selecting the first LO frequency to be outside of the first signal channel, the first LO frequency may be used as a mixing

15 signal to provide down conversion of the first signal channel to a frequency range around DC. A resulting tuned analog signal may then be subjected to digital fine tuning, for example, using digital fine tune circuitry 104 of FIG. 1C.

28

In various embodiments, the first LO frequency may be selected to be further outside of the first signal channel by at least a first amount $f_{noise-offset}$ to avoid the effects of 1/f noise and DC offset errors.

5   Still referring to FIG. 3A, it may later be desired by a user of the satellite receiver to concurrently tune into a second signal channel, for example, for use with PnP, DVR, or the like. In such an embodiment, a selection signal may be received for the second signal channel (block

10   315). A second LO frequency may then be selected for the second signal channel that is outside of the second signal channel and that also does not interfere with the first LO frequency (block 320). That is, the second LO frequency should be selected such that the VCO that generates the

15   second LO frequency does not interfere with the VCO that generates the first LO frequency.

Referring now to FIG. 3B, shown is a flow diagram of a method for tuning a second signal channel in a satellite receiver in accordance with an embodiment of the present

20   invention. FIG. 3B may be used in selecting LO frequencies for a two tuner receiver, and further details how to select the second LO frequency to avoid interference with the first LO frequency. As shown in FIG. 3B, method 325 begins by receiving a selection signal for a second signal channel

25   (block 330).

29

It may be determined whether the second signal channel is near the first signal channel (diamond 335). In this embodiment, "near" means that the two signal channels are close enough in frequency that undesired interference may

5   occur if a LO frequency is not carefully selected. For example, two signal channels may be near each other if $f_{separate}$ for the first LO frequency extends into either LO frequency selection region of a second signal channel. While what is considered to be near a given signal may vary

10   in different embodiments, in certain embodiments, a second channel may be considered to be near a first channel if is within between approximately 50 MHz and 80 MHz of the first channel.

If it is determined that the second signal channel is

15   not near the first signal channel, the second LO frequency may be selected from available LO frequencies for the second signal channel (block 340). For example, in such instance the second LO frequency may be selected from either of a first and second LO selection region

20   surrounding the second signal channel.

If instead it is determined that the second signal channel is near the first signal channel, the second LO frequency must be selected carefully so as to avoid interference between the two VCOs. As shown in FIG. 3B,

25   the second LO frequency may be chosen from the LO frequency selection regions for the second channel and further be

chosen such that it is outside the crosstalk region of the first LO (block 350). In such manner, the second LO frequency will not interfere with the first LO frequency, i.e., the two VCOs generating the LO frequencies do not

5   create crosstalk.

Referring now to FIG. 3C, shown is a flow diagram of a method for selecting a LO frequencies for second and third signal channels in accordance with an embodiment of the present invention for use with a three tuner satellite

10 receiver. For example, such a receiver may be a three tuner system without multiplexers.

As shown in FIG. 3C, method 360 begins by receiving a selection signal for a second signal channel (block 361). While not shown in FIG. 3C, it is to be understood that

15 prior to selection of a second signal channel, a first signal channel has been tuned using a first LO frequency. Then the second LO frequency may be carefully selected (block 362). More specifically, the second LO frequency may be selected to both avoid interference with an existing

20 first LO frequency and further be carefully selected such that it is at least a predetermined distance away from the first LO frequency. In such manner, corner cases and a worst case scenario, as discussed above with regard to FIG. 2C may be avoided. Specifically, in various embodiments,

25 the second LO frequency may be selected to avoid certain LO frequencies, namely those that are $NL_{fseparate} + Nl_{fw} + 1$ to

$Nl_{fseparate} + Nsf_W + NLf_{separate} \cdot f_{LO\text{-}step}$ away from the first LO
frequency. In such manner, a worst case situation may be
avoided if a third signal channel is desired to be used in
the three tuner receiver system.

5   Then a selection signal for a third signal channel is
received (block 365). Next it may be determined whether
the third signal channel is near either of the first or
second signal channels (diamond 370). As discussed above,
in this instance near means whether it is close enough in
10   frequency that undesired interference may occur if a LO
frequency is not carefully selected (e.g., if $f_{separate}$ for
either of the pending channels extends into a LO selection
region for the third signal channel).

       If the third signal channel is not near either the
15   first or second signal channels, the third LO frequency may
be selected from the available LO frequencies for the third
signal channel (block 375). That is, if the third signal
channel is far enough away from both of the first and
second channels, the third LO frequency may be selected
20   from either of a first or second LO frequency selection
region for the third signal channel.   \

       Alternately, if it is determined that the third signal
channel is near one or both of the signal channels, it may
then be determined whether the third signal channel is
25   between the first and second signal LO frequencies (diamond
380). If the third signal channel is not in between the

two existing LO frequencies, the third LO frequency may be carefully selected to avoid interference with the first or second LO frequencies and be a predetermined distance away from the first or second LO frequencies (block 385).

5   If instead the third signal channel is between the LO frequencies for the first and second channels, the third signal channel may choose an available LO frequency that is apart from the first and second LO frequencies by at least $f_{separate}$ (block 390). In alternate embodiments, for example,

10   where multiplexers are present in a receiver having multiple tuners (e.g., a three tuner system), a LO frequency for the third channel may be multiplexed from one of the first or second LO frequencies.

While discussed herein, for example, for a two tuner

15   system, receiving a first selection signal for a first channel, a second selection signal for a second channel and so forth, it is to be understood that in other embodiments a first signal may be received and a first channel tuned, then a second channel tuned. However, the first channel

20   may then be turned off, and at a later time a third channel may be desired to be tuned. In such embodiments, the LO frequency for the third channel may be selected in light of the existing second channel but not the original first channel that is no longer being tuned. Further, all

25   parameters relating to the second channel may be maintained unchanged while tuning the third signal channel.

Referring now to FIG. 3D, shown is a flow diagram of a method for selecting LO frequencies for four or more signal channels. As shown in FIG. 3D, method 391 begins by receiving selection signal for the N signal channels (block 392). The LO frequency for the first signal channel may be selected to be outside of that signal channel (block 393). As discussed above, this frequency may also be selected to be outside of a noise-offset region surrounding the first LO frequency. Next, the LO frequency for the N+1 signal channel may be selected to be outside of that signal channel (and also outside of a noise-offset region thereof) (block 394). For example, $f_{LO-step}$ may be greater than $f_{separate}$ such that additional signal channels may select a LO frequency that does not interfere with an existing LO frequency. Otherwise, one of the earlier LO frequencies may be selected and multiplexed for the N+1 signal channel. Next, it may be determined whether additional signal channels are desired (diamond 395). If so, N is set equal to N+1 (block 396) and control returns to block 394.

Such methods may improve the performance and efficiency of a receiver architecture by providing multiple LO frequencies and helping to resolve multiple channels whose frequencies are relatively close to each other.

It is often desirable to include two or more receivers in a single integrated circuit and to reduce the frequency range within which the digital fine tune circuitry 104 must

34

operate. Also, as discussed above, it is advantageous to increase the frequency step between LO frequencies ($f_{LO-step}$) so that adjacent LO frequencies from two or more separate receivers in an integrated multi-tuner satellite receiver

5   are far enough apart to avoid interference with each other. However, it is also advantageous to reduce $f_{LO-step}$ to reduce the frequency range within which the digital fine tune circuitry 104 must operate and to relax the design specifications for the digital fine tune circuitry 104,

10   including, for example, low pass filter (LPF) circuitry and analog-to-digital conversion (ADC) circuitry. Thus, in certain embodiments, a frequency step between 5 and 50 MHz may be selected as a $f_{LO-step}$, and in one particular embodiment, a $f_{LO-step}$ of 10 MHz may be selected. Other

15   frequency steps may be reasonable choices when considering the trade-off between minimizing the frequency step while still keeping adjacent LO frequencies separated to avoid interference. Of course, other frequency steps or configurations may be chosen depending upon the particular

20   design requirements involved.

FIG. 4 is an example implementation for a basic receiver architecture using a wide-band ADC for the digital fine tune circuitry 104. In particular, embodiment 400 of FIG. 4 utilizes a wide-band ADC 402 that receives coarsely

25   tuned signal 110 and provides a digital output to a tunable digital filter 404, which in turn outputs the digital

baseband signals 112. For fine tuning the desired channel within the signal 110, the tunable digital filter 404 utilizes a variable frequency (f_V) 406 generated, for example, by a numerically controlled oscillator (NCO) 408

5   that in turn receives the center frequency (f_{CH}) 114 for the desired channel.

By fine tuning the coarsely tuned channel spectrum, the receiver 400 does not mix the desired channel down to a fixed target IF frequency and then mix the desired channel

10   to DC. Rather, this implementation uses the analog coarse tune circuitry 102 to mix the desired channel down to a variable location within a frequency range around DC, and then digital conversion and digital filtering is performed directly on this coarsely tuned channel spectrum.

15   FIG. 5 is a block diagram of an embodiment 500 for a two receiver architecture located on a single integrated circuit. In general, this embodiment 500 duplicates the circuitry of FIG. 1C to produce a dual receiver architecture. The first receiver includes analog coarse

20   tune circuitry 102A, large-step LO1 circuitry 106A (which outputs a first LO mixing frequency (f_{LO1})116A), and digital fine tune circuitry 104A (which receives a first center frequency (f_{CH1}) 114A for a first desired channel to be tuned). As discussed above, the first receiver coarsely

25   tunes the input channel spectrum 108A to produce the intermediate coarsely tuned channel signal 110A and then

digitally processes this signal to finely tune the channel
and to produce digital baseband signals for the first tuner
output 112A. Similarly, the second receiver includes
analog coarse tune circuitry 102B, large-step LO2 circuitry

5   106B (which outputs a second LO mixing frequency
(f_{LO2})116B), and digital fine tune circuitry 104B (which
receives a second center frequency (f_{CH2}) 114B for a second
desired channel to be tuned). The second receiver coarsely
tunes the input channel spectrum 108AB to produce the

10 intermediate coarsely tuned channel signal 110B and then
digitally processes this signal to finely tune the channel
to produce digital baseband signals for the second tuner
output 112B. By using embodiments of the present
invention, LO frequencies for the two tuners may be

15 selected to avoid interference, precluding the need for a
multiplexer.

        The architecture of the present invention may be
utilized to integrate additional receivers within a single
integrated circuit. For example, if four tuners were

20 utilized, additional receiver circuitry could be integrated
with that shown in FIG. 5 to provide additional analog
coarse tuning circuitry, digital fine tuning circuitry and
LO circuitry for a third receiver and additional analog
coarse tuning circuitry, digital fine tuning circuitry and

25 LO circuitry for a fourth receiver. As discussed above, a
variety of selection techniques could be implemented for

37

the LO frequencies provided by the different LO circuitries
with respect to the multiple receivers such that
interfering overlaps of the LO mixing frequencies could be
avoided.

5   Referring now to FIG. 6, shown is a block diagram of a
satellite receiver in accordance with an embodiment of the
present invention with four recievers. As shown in FIG. 6,
the receiver 600 includes four tuners 600a-600d. For
simplicity, first tuner 600a and fourth tuner 600d are
10   shown in detail, and second tuner 600b and third tuner 600c
are shown as blocks. However, it is to be understood that
each of the four tuners shown in FIG. 6 may include similar
tuning circuitry to that shown in first tuner 600a and
fourth tuner 600d.

15   As shown in FIG. 6, each tuner includes its own large
step LO circuitry 606 that may be used to generate a LO
frequency. In accordance with an embodiment of the present
invention, each of the large step LO circuitries 606a-d may
be coupled to a multiplexer 620a-d (i.e., MUX 1-4).
20   Multiplexers 620a-d may receive control signals (not shown
in FIG. 6) from a large step LO circuitry 606 or another
location in satellite receiver 600 so that it may select an
appropriate one of the LO frequencies for use in the given
tuner. For example, multiplexers 620a-d may be used to
25   select, for example a LO frequency generated by large step
LO circuitry 606a for use in multiple tuners.

While not shown in FIG. 6, it is to be understood that large step circuitry 606 or another location in satellite receiver 450 may receive information regarding presently existing signal channels and LO frequencies used therein,

5 which may be used by an algorithm discussed above to determine a LO frequency for an additional signal channel.

Furthermore, in certain embodiments, various parameters may be determined ahead of time for a satellite receiver, for example, during design, development and/or

10 initial programming thereof. Such parameters may be stored in a nonvolatile memory in satellite receiver 600. Such parameters may include, in certain embodiments a bandwidth of a widest signal channel within a signal spectrum (i.e., f_{WW}), a step frequency (i.e., $f_{LO-step}$), and a separation

15 frequency to avoid crosstalk (i.e., $f_{separation}$). In such embodiments, using these parameters, in addition to the known frequency and LO frequency of a first signal channel and frequency of a desired second signal channel, a LO frequency for the second channel may be determined that

20 does not interfere with the LO frequency of the first channel. Similarly, additional signal channels may be acquired using additional LO frequencies or a present LO frequency to similarly avoid interference.

Thus in various embodiments having any number of

25 tuners within a receiver, 1/f noise and DC offset noise may be eliminated, crosstalk between VCO's may be avoided, and

an input signal frequency error (i.e., an LNB error) may be canceled. Further in embodiments having two tuners, no MUX is needed, which simplifies system design, and avoids the harmonic of one VCO affecting another VCO.

5   While the present invention has been described with respect to a limited number of embodiments, those skilled in the art will appreciate numerous modifications and variations therefrom. It is intended that the appended claims cover all such modifications and variations as fall

10   within the true spirit and scope of this present invention.